



VDAO40P Technical Specifications

- **Manufacturer Name:**
Bierer & Associates, Inc. Blythewood, S.C. USA
- **Product Name:**
VDAO40P
- **Product Properties:**
Shielded Housing, 24Mega Ohm Probe, Self Test Feature in the “T” switch position, Switch positions Calibrated for Height above Ground.
- **Functional Description:**
Multi-functional Voltage Detector, Highly Sensitive Proximity position, Calibrated URD and OH Voltage Detection positions allow for more Accurate readings.
- **Minimum Operating Temperture:**
0 degree Fahrenheit (-18 degrees Celsius)
- **Maximum Operating Temperture:**
120 degrees Fahrenheit (49 degrees Celsius)

- **AC specifications:**

500 volts – 40kV

- **Physical Dimensions:**

Meter Probe, 14.5 in. long (36.8 centimeters) X 4 in. wide (10.2 centimeters) X 7 in. high (17.8 centimeters)

- **Weight:**

2 lbs. (.9 kilograms) Meter Probe

- **Applications:**

Traditional Voltage Detection with better accuracy than conventional Voltage Detectors, along with a Proximity Function to check for EMF emitting from Capacitive Test Points, Failed URD drain wire connections, “Hot or Not” Secondary and Primary voltage Indication